

IN THE CLAIMS:

The following is a complete listing of all pending claims.

1. (Previously Presented) An image transmission system for a mobile robot,
comprising:

a camera for capturing an image as an image signal;

human detecting means for detecting a human from the captured image;

a power drive unit for moving the entire robot toward the detected human;

face identifying means for identifying a position of a face of the detected human;

face image cut out means for cutting out a portion of the captured image of the
detected human so that the portion of the image includes a face image of the detected
human;

image transmitting means for transmitting only the cut out portion of the image
including the face image to an external terminal; and

means for monitoring state variables comprising a current position of the robot,
the image transmitting means transmitting the monitored state variables in addition to the
cut out face image.

2. (Cancelled)

3. (Original) An image transmission system according to claim 1, wherein the robot is adapted to direct the camera toward the position of the face of the detected human.

4. (Original) An image transmission system according to claim 1, further comprising means for measuring a distance to each of a plurality of humans, the human detecting means being provided with means for detecting a human closest to the robot.

5. (Original) An image transmission system according to claim 1, wherein the mobile robot is adapted to move toward the detected human according to a distance to the detected human.

6. (Original) An image transmission system according to claim 1, further comprising a face database that stores images of a plurality of faces and face identifying means for comparing the cut out face image with the faces stored in the face database to identify the cut out face image.

7. (Original) An image transmission system according to claim 1, wherein the face identifying means comprises means for detecting an outline of the detected human, and identifying a face as an area defined under an upper part of the outline of the detected human.

8. (Original) An image transmission system according to claim 1, wherein the human detecting means is adapted to detect a human as a moving object that changes in position from one frame of the image to another.

9. (Previously Presented) An image transmission system according to claim 1, wherein the face image of the detected human occupies a substantially entire area of the cut out portion of the image.

10. (Previously Presented) An image transmission system for a mobile robot, comprising:

a camera for capturing an image as an image signal;

human detecting means for detecting a human from the captured image;

a power drive unit for moving the entire robot toward the detected human;

image cut out means for cutting out a portion of the captured image so that the portion of the image includes an image of the detected human according to information from the camera;

image transmitting means for transmitting only the cut out portion of the image including the human image to an external terminal; and

means for monitoring state variables comprising a current position of the robot,
the image transmitting means transmitting the monitored state variables in addition to the
cut out face image.